


Specifications //



Technical Data //

| | |
|-----------------------|--|
| Voltage, Power Input | 48 V DC $\pm 10\%$, 240 W (Option: 24 V DC $\pm 5\%$, 75 W, with reduced max. speed of 8000 rpm) |
| Temperature Range | Ambient and gas temperature range 0 to 40° C |
| IP Rating | IP67 |
| Electrical Interfaces | PLC with: 2 analog inputs 4--20 mA / 1 analog output 4-20 mA / 2 digital inputs 0-24 V (optocoupler) 2 digital outputs 0-24 V / 100 mA (open drain) RS485 interface, Modbus protocol (extended control or service through fieldbus or Levitronix Service Software) |
| Standard Firmware | V3.16x |
| Mechanical Interface | Mounting hole on bottom of motor, $\varnothing 96$ mm, mounting ring included |
| Cable Length | 5 m + 0.2 m wires with TE connectors for power and PLC signals |
| Materials | Polypropylene, Cable: PVC jacket, PVDF bushing |
| Weight | 1.3 kg, 2.9 lb (for 5 m version) |

Headquarter and European Contact

Levitronix GmbH
Bändliweg 30
CH-8048 Zurich
Switzerland

+41 44 974 4000
salesEurope@levitronix.com

US Contact

Levitronix Technologies Inc.
10 Speen Street, Suite 102
Framingham
Massachusetts 01701 USA

+1 508 861 3800
salesUS@levitronix.com

Japan Contact

Levitronix Japan K.K.
Wing Eight 5floor, 4-16-4
Asakusabashi, Taito-ku
Tokyo, 111-0053 Japan

+81 3 5823 4193
salesJapan@levitronix.com

Taiwan Contact

Levitronix Taiwan
Rm. 3, 8F., No.38, Taiyuan St.Zhu-
bei, City, Hsinchu County 302 Taiwan
R.O.C.

+886 3 657 6209
salesAsia@levitronix.com

© Levitronix | Levitronix_Brochure_PURO_Rev01
Creation Date: 2025-03-18 | Last Update: 2025-03-18

LEVITRONIX®
PURO™

ACTIVE
ASEPTIC
DISTRIBUTION
OF VHP

BOOST YOUR BIODECON- TAMINATION CYCLE



The Levitronix® PURO™ MagLev fan is designed for aseptic and powerful distribution of Vaporized Hydrogen Peroxide (VHP).

Based on active magnetic levitation, the fan impeller is suspended in the air and driven by the magnetic field of the motor. The constant gap between rotor and stator ensures that there is no wear and therefore virtually no particle contamination. Unlike conventional fans with a mechanical bearing, there are no lubricants or seals. This makes Levitronix® PURO™ the only fan technology to be installed in highly critical environments such as Isolators, pharma grad A clean rooms or other aseptic areas.

Since there is no mechanical bearing, the Levitronix® PURO™ can be operated at extremely high speeds to ensure VHP decontamination over a wide area and in hard-to-reach areas such as glove boxes or complex filling machines. The fan rotor can be operated at both positive and negative speeds, as well as in fast pulse mode to further increase turbulence. To clean the Levitronix® PURO™, the rotor can simply be pulled out and placed back in.

ADVANTAGES OF LEVITRONIX® PURO™

No Particle Contamination //

certified for pharma grade A*

Since there is no mechanical contact between fan rotor and motor, there is no wear and therefore no particle contamination.

Extremely Powerful //

up to 10'000 rpm

Since there is no mechanical bearing and thus no friction, the Levitronix® PURO™ can be operated at extremely high speeds.

Ab- and Desorption Free //

100% high-performance plastic

There is no other material in contact with VHP than non-absorbing* high-performance plastic.

No Lubricants or Sealings //

no risk of contamination

Unlike conventional fans with ball or slide bearings, a magnetic bearing does not require lubricants or sealings.

Chemically Resistant //

robust against VHP*


There is no other material in contact with VHP than non-absorbing* high-performance plastic.

Maintenance-free //

Extremely high reliability

There is no bearing to fail or sealing to wear out which results in highest reliability.

Magnetic field

A diagram showing a magnetic field with red dots and arrows pointing towards a central point.

The Levitronix® PURO™ comes with a mounting ring and a screw set, allowing for easy installation into isolator walls